

UNCLASSIFIED

AD 401 573

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

401 573

⑤ 17511

u

S/198/62/008/005/003/009
D234/D30810.5600
STEP

AUTHORS: ⑧ Pryvarnykov, A. K. and Shevlyakov, Yu. A.

TITLE: ⑥ Contact problem for a many-layer base

PERIODICAL: ⑤ Akademiya nauk Ukrayins'koyi RSR. Instytut mekhaniky.
Prykladna mekhanika, v. 8, № 5, 1962, 508-515

TEXT: The base is assumed to consist of an arbitrary number of layers having different elastic properties, each with constant thickness. It is also assumed that no gaps are formed between the layers during deformation, the deformation is plane, the displacements are equal to zero at infinity, the state of loading is symmetrical with respect to the x axis, the stress functions and their derivatives up to the fourth order satisfy the conditions of existence of Fourier's sine and cosine transformations. Recurrence formulas are given which make it possible to solve the basic problems of the theory of elasticity for bases consisting of any number of layers, if two image functions for one of these layers can be found. The authors consider the case when the lowest layer is placed on a rigid

Card 1/4

Contact problem for ...

S/198/62/008/005/003/009
D234/D308

surface and a symmetrical die acts on the top layer. The image function $\alpha(p)$ for the top layer is sought in the form

$$\alpha(p) = \frac{1}{lp^2} \int_0^a \chi(t) J_0(pt) dt \quad (2.5)$$

J_0 denoting the cylindrical function of the first kind. The problem is reduced to a Fredholm integral equation

$$\chi(x) = \frac{E}{2(1-\nu^2)} \left[y'(0+x) \int_0^{\frac{\pi}{2}} y''(x \sin \gamma) d\gamma \right] + \int_0^a \chi(t) K(x,t) dt \quad (2.11)$$

Card 2/4

Contact problem for ...

S/198/62/008/005/003/009
D234/D308

where $y(x)$ is a function determining the shape of the die, and

$$K(x, t) = x \int_0^{\infty} p \varphi(p) J_0(px) J_0(pt) dp \quad (2.12)$$

$$\varphi(p) = 1 - \frac{A(p)}{1} \quad (2.8)$$

$$B_1 = \alpha_1 p A(p) \quad (1.6)$$

[-Abstracter's note: 1 not defined, probably Eq. (2.6) in which the left hand side is missing.] The image functions α and B were defined by the authors in a previous paper (Prykladna mekhanika, v. 8, 1962, no. 2), $2a$ is the maximum width of the die. When the layer thickness tends to ∞ one obtains the solution for a half-plane

Card 3/4

Contact problem for ...

S/198/62/008/005/003/009
D234/D308

[-Abstracter's note: The meaning in which the authors use this term is not clear.] Eq. (2.11) is reduced to a form suitable for numerical computation. Tables of auxiliary coefficients which do not depend on the shape of the die are given for the case of a layer placed on a half-plane and on a rigid base. The method of computation is described and the results quoted for the two above cases, the die being round and the contact segment four times as large as the layer thickness. The forces P have the form $P = m E a^2 / (1 - \nu^2) R$. The radius of the die R is assumed to be sufficiently large. The coefficient m is equal to 0.21 for a layer on a half-plane and to 0.51 for a layer on a rigid base. There are 2 tables and 1 figure.

ASSOCIATION: Dnipropetrovs'kyi derzhavnyi universytet (Dnipropetrovsk State University)

SUBMITTED: March 10, 1962

Card 4/4